



Cordless mixing – at long last. State-of-the-art technology to suit professional requirements

Independence during mixing work, without being dependent on the nearest socket outlet. Mix wherever the material is being processed: in the underground car park, on the scaffolding, in the shell, in the courtyard or in the open countryside.

The powerful 18 V, 5.2 Ah Li-ion battery of the Collomix **Xo 10** NC ensures sufficient range and torque, even with denser and plastic materials such as ready-mixed mortar



or adhesives.

The cordless mixer cuts an impressive figure with excellent ergonomics for uncramped and comfortable working. Ergonomically adapted handles mean the machine sits well in your hands. And with Collomix's very own HEXAFIX coupling, you can change the mixer in next to no time.

Electronic speed regulation using the electronic switch with a safety on/off function enables smooth acceleration and clean working. When operating at full power, the electric motor unleashes surprisingly high forces for optimum homogenisation of the materials.

A range of mixes that weren't previously achieved are available with the 5.2 Ah lithium-ion battery. This is also determined by the viscosity of the mixed material used.

The combination of the Collomix hand mixers' acknowledged expertise and reliability and the Metabo battery system offers professionals the top technology and reliability they have come to expect from a leading brand.





Machine features



The Xo 10 NC's Metabo battery system





"AIR COOLED" Li-ion battery fixture battery packs

- Metabo's Ultra-M technology: intelligent battery management for long-life battery packs with three-year guarantee
- Patented "AIR COOLED" charging technology for shorter charging times
- Permanent electronic single cell monitoring (ESCP) when charging, for a particularly long service life
- Processor-controlled charge and discharge management
- Optical capacity indicator for permanent checking of the capacity status
- No memory effect
- Long shelf life with next to no self-discharge

Sample applications



EP coating / paints



Self-levelling compound



Slurry



Natural stone mortar



Tile adhesive



Grout



Adhesive and reinforcing mortar



Egalisation filler

Suitable mixers



WK 120 HF for ready-mixed mortar, plaster, screed, medium-bed and thick-



KR 120 HF for tile and adhesive mortar, filler, grout



DLX 120 HF for self-levelling compounds, sludges, thin-bed mortar



LX 120 HF for paints, coatings, sealings

Technical data for Xo 10 NC

First gear load speed	-640 rpm
Set mixer	WK for ready-mixed mortar, plaster, screed
Max. mixer Ø	120 mm
Mixer connection	HEXAFIX quick coupling
Max. mixed quantity	- 40 ltr.
Metabo battery pack	18 V, 5.2 Ah Li-ion
Charging time for battery Ø	Approx. 100 min.
Scope of delivery	20490 Xo 10 $^{\rm NC}$ set with one 18 V, 5.2 Ah battery, charger and WK 120 HF mixer
Scope of delivery	20492 (KAR) Xo 10 NC with WK 120 HF mixer not including 18 V, 5.2 Ah battery and charger





