## > TMX 1000 forced-action mixer Collomix

lomix



## The TMX 1000 forced-action pan mixer

is the right choice, when it comes to mixing prebagged material at the construction site

## > Materials and applications



## TMX 1000 forced-action mixer

- Sturdy mixer for prebagged material with usable volumes of up to 80 litres (up to 4 sacks)
- For all types of plastic mortar, plaster, screed and concrete (-16 mm), the mixing tool can also be removed without requiring any other tool
- Bottom segment slidegate for emptying contents into a bucket or wheelbarrow
- Adapter for vacuum cleaner, for dust-free work
- Safety shut-down and lid detection
- Hard rubber wheels, therefore extremely stable
- Lashing eyes

 $\mathbf{O}$ 

Terrazzo (TMX 1000 TZ)

Your Collomix specialised dealers:

- Compact size, fits though 80-cm-wide doors
- Easy to clean, extendible outlet shaft
- Robust design and motor protected from dirt
- Easy to clean, extendible outlet shaft
- TMX 1000 TZ model specially designed for terrazzo





Removable discharge chute •



Dust extraction



Material (weight without the addition of water)		TMX 1000 technical data		
Concrete up to 16 mm grain size	•	Capacity:	100 litres	
Cement screed	<b>•</b>	Usable volumes:	80 litres	
Synthetic resin screed (2K, 0.6/1.2 mm)	0	Motor output:	2.0 kW	
Cement and universal mortar	0	Voltage:	230 V / 50 Hz	
Lightweight masonry mortar	<b>C</b>	Speed of mixing tool:	30 rpm <sup>-1</sup>	
Cement plaster	0	Height to bottom edge of discharge chute:	625 mm	
Gypsum plaster	•	Dimensions:	840 x 755 x 1,170 mm	
Heat insulation plaster	<b>C</b>	Noise emissions:	86 dB	
Natural stone mortar/cobblestone mortar	0	Weight:	131 kg	
2K pavement grout (up to 1.2 mm)	0	Item no.:	37080	
thin/fluid screed types	•			
thin/fluid mortar types	•	TMX 1000 TZ technical data (with special mixing tool for terrazzo)		
Tile adhesive	•		, , , , , , , , , , , , , , , , , , ,	
Grout	•	Capacity:	100 litres	
Levelling compounds/self-levelling fillers	•	Usable volumes:	80 litres	
Packing mortar	<b>•</b>	Motor output:	2.0 kW	
Steel fibre mortar	0	Voltage:	230 V / 50 Hz	
Lightweight aggregate	<b>•</b>	Speed of mixing tool:	30 rpm-1	

**Dimensions:** 

Weight:

Item no.:

Noise emissions:

Height to bottom edge of discharge chute:

Collomix GmbH | Daimlerstr. 9 | 85080 Gaimersheim | Germany Tel. (08458) 32 98 0 | Fax (08458) 32 98 30 | info@collomix.de | www.collomix.com

0



625 mm

86 dB

131 kg

37084

840 x 755 x 1,170 mm